

We MERSEN USA EP Corp.
374 Merrimac Street Newburyport, MA 01950 USA

Certify that products with the registered trade mark Mersen Ferraz Shawmut

Product type Medium Voltage IEEE Fuses
Back-Up R-Rated Ferrule Mount Fuses for Motor Protection

Model Series Line 2.5 kV Ferrule Mount Motor

References please refer to page 2 for catalog number

comply with the EU RoHS (Restriction of Hazardous Substances) Directives:

RoHS directive N° 2011/65/UE

RoHS directive N° 2015/863

https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Any exemptions are listed below and exemption validity dates are monitored by Mersen.

The information provided below is based on data obtained through ongoing due diligence with our suppliers. In some cases, the information may not yet represent full coverage of our supply chain. Mersen reserves the right to update or amend this declaration as additional data becomes available, or verification processes are completed.

This declaration is not an EU or UKCA declaration of conformity, Mersen USA EP Corp. is providing RoHS conformity to all product ranges even if they are out of the scope of the directive with the same level of compliance on substances restrictions and corresponding exemptions.

Date / Location : 17.02.2026 / Newburyport

Name : Tim KAPPEN

Position / Signature :

Sr. Manager Quality
For the president and by delegation



COMP-015255

Catalog number list

Item number	ROHS exemption
A240R5R	6(c) - Copper alloy containing up to 4% lead by weight
A240R2R	6(c) - Copper alloy containing up to 4% lead by weight
A240R1R	6(c) - Copper alloy containing up to 4% lead by weight
A240R3R	6(c) - Copper alloy containing up to 4% lead by weight
A240R4R	6(c) - Copper alloy containing up to 4% lead by weight
A240R6R	6(c) - Copper alloy containing up to 4% lead by weight
A240R9R	6(c) - Copper alloy containing up to 4% lead by weight
A240R12R	6(c) - Copper alloy containing up to 4% lead by weight
A240R18R	6(c) - Copper alloy containing up to 4% lead by weight
A240R24R	6(c) - Copper alloy containing up to 4% lead by weight
A240R36R	6(c) - Copper alloy containing up to 4% lead by weight
9F60LCB502	
9F60LCB503	
9F60LCB504	
9F60LCB506	
9F60LCB509	
9F60LCB512	
9F60LCL302	6(c) - Copper alloy containing up to 4% lead by weight
9F60LCL303	6(c) - Copper alloy containing up to 4% lead by weight
9F60LCL304	6(c) - Copper alloy containing up to 4% lead by weight
9F60LCL306	6(c) - Copper alloy containing up to 4% lead by weight
9F60LCL309	6(c) - Copper alloy containing up to 4% lead by weight
9F60LCL312	6(c) - Copper alloy containing up to 4% lead by weight
9F60MCB518	
9F60MCB524	
9F60MCL318	6(c) - Copper alloy containing up to 4% lead by weight
9F60MCL324	6(c) - Copper alloy containing up to 4% lead by weight