RoHS COMPLIANCE STATEMENT

We MERSEN USA EP Corp.
374 Merrimac Street Newburyport, MA 01950 USA

Certify that products with the registered trade mark Mersen Ferraz Shawmut

Product type High-Speed and Semiconductor protection fuses
Round Body High-Speed Fuse-Links AC Protection

Model Series Line Amp-Trap® A60X 600VAC

References please refer to page 2 for catalog number

comply with the EU RoHS (Restriction of Hazardous Substances) Directives:
RoHS directive N° 2011/65/UE
RoHS directive N° 2015/863
https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Any exemptions are listed below and exemption validity dates are monitored by Mersen.

The information provided below is based on data obtained through ongoing due diligence with our suppliers. In some cases, the information may not yet represent full coverage of our supply chain. Mersen reserves the right to update or amend this declaration as additional data becomes available, or verification processes are completed.

This declaration is not an EU or UKCA declaration of conformity, Mersen USA EP Corp. is providing RoHS conformity to all product ranges even if they are out of the scope of the directive with the same level of compliance on substances restrictions and corresponding exemptions.

Date / Location : 19.05.2026 / Newburyport

Name : Tim KAPPEN

Position / Signature : Sr. Manager Quality
For the president and by delegation Tim Kappen

COMP-016690

Catalog number list

Item number	ROHS exemption
A60X65-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X90-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X80-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X70-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X100-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X100-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X70-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X80-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X90-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X80-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X100-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X70-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A60X1000-128	6(c) - Copper alloy containing up to 4% lead by weight
A60X1200-128	6(c) - Copper alloy containing up to 4% lead by weight
A60X1000-128IL	6(c) - Copper alloy containing up to 4% lead by weight
A60X1200-128TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X150-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X200-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X125-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X175-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X200-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X125-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X175-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X150-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X125-4TA	6(c) - Copper alloy containing up to 4% lead by weight

A60X200-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X150-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X200-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A60X1600-128	6(c) - Copper alloy containing up to 4% lead by weight
A60X2000-128	6(c) - Copper alloy containing up to 4% lead by weight
A60X1500-128	6(c) - Copper alloy containing up to 4% lead by weight
A60X1800-128	6(c) - Copper alloy containing up to 4% lead by weight
A60X1600-128TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X1800-128TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X1500-128TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X2000-128TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X4-1	
A60X1-1	
A60X12-1	
A60X2-1	
A60X5-1	
A60X6-1	
A60X7-1	
A60X10-1	
A60X15-1	
A60X20-1	
A60X25-1	
A60X30-1	
A60X3-1	
A60X8-1	
A60X2500-128	6(c) - Copper alloy containing up to 4% lead by weight
A60X3000-128	6(c) - Copper alloy containing up to 4% lead by weight
A60X3000-128TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X2500-128TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X400-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X300-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X225-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X250-4	6(c) - Copper alloy containing up to 4% lead by weight

A60X350-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X250-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X300-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X225-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X400-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X350-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X300-4K-TI	6(c) - Copper alloy containing up to 4% lead by weight
A60X250-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X350-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X225-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X300-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X400-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X400-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A60X300-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A60X250-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A60X40-4	
A60X45-4	
A60X50-4	
A60X35-4	
A60X60-4	
A60X55-4	
A60X600-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X500-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X450-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X450-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X500-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X600-4K	6(c) - Copper alloy containing up to 4% lead by weight
A60X500-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X600-4TA	6(c) - Copper alloy containing up to 4% lead by weight

A60X450-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X500-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A60X600-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A60X700-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X800-4	6(c) - Copper alloy containing up to 4% lead by weight
A60X700-128	6(c) - Copper alloy containing up to 4% lead by weight
A60X800-128	6(c) - Copper alloy containing up to 4% lead by weight
A60X800-128TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X700-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A60X800-4TA	6(c) - Copper alloy containing up to 4% lead by weight