RoHS COMPLIANCE STATEMENT

We MERSEN FRANCE SB
15, Rue Jacques de Vaucanson 69720 SAINT BONNET DE MURE FRANCE

Certify that products with the registered trade mark Mersen

Product type High-Speed and Semiconductor protection fuses
Square Body High-Speed Fuse-Links DC Protection

Model Series Line Protistor® size 122 gR, 750VDC

References please refer to page 2 for catalog number

comply with the EU RoHS (Restriction of Hazardous Substances) Directives:
RoHS directive N° 2011/65/UE
RoHS directive N° 2015/863
https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Any exemptions are listed below and exemption validity dates are monitored by Mersen.

The information provided is based upon data obtained from ongoing due diligence concerning goods and materials provided by our suppliers. Mersen reserves the right to update and modify this communication, as it believes necessary or appropriate.

Date / Location : 17.04.2026 / Saint Bonnet de Mure

Name : Pierre LAVAUD

Position / Signature : Head of R&D department
For the president and by delegation
Pierre Lavaud

COMP-016098

Catalog number list

Catalog number	Item number	ROHS exemption
D122GC75V250EF	A087331	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D122GC75V315EF	B087332	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D122GC75V350EF	W221141	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D122GC75V400EF	L089388	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D122GD75V450EF	P220951	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D122GD75V500EF	Q220952	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D122GC75V250TF	B090437	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D122GC75V315TF	M085249	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D122GC75V350TF	G220898	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D122GC75V400TF	C090438	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D122GD75V450TF	R220953	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D122GD75V500TF	S220954	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)